

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
18 April 2002 (18.04.2002)

PCT

(10) International Publication Number  
**WO 02/032072 A3**

(51) International Patent Classification<sup>7</sup>: **H04L 12/18**  
12/24

(74) Agents: **TROP, Timothy, N. et al.**; Trop, Pruner & Hu,  
P.C., 8554 Katy Freeway, Suite 100, Houston, TX 77024  
(US).

(21) International Application Number: PCT/US01/31161

(22) International Filing Date: 3 October 2001 (03.10.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/686,754 10 October 2000 (10.10.2000) US

(71) Applicant (for all designated States except US): **INTEL CORPORATION** [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **HUSKINS, Jeffrey** [US/US]; 1931 West Bartlett Court, Chandler, AZ 85248 (US).

Published:

— with international search report

[Continued on next page]

(54) Title: METHOD AND SYSTEM FOR MANAGING REMOTE CLIENTS IN A NETWORK CONSTITUTED BY A CENTRAL SERVER WHICH IS LINKED TO REMOTE CLIENTS



(57) Abstract: A messaging system may enable a server to assign unique identifiers to a plurality of clients. These identifiers enable a client to determine whether a message is specifically targeted to that client or, as an alternative, whether the client is a member of a group of targeted clients. A server may send messages containing an identifier to agents on one or more clients. The identifier may specify commands to manage the uploading of information from one or more clients to a server.



(88) Date of publication of the international search report:  
6 February 2003

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 01/31161

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L12/18 H04L12/24

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC, IBM-TDB, COMPENDEX

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>US 5 978 845 A (REISACHER OLIVIER MICHEL) 2 November 1999 (1999-11-02)</p> <p>column 5, line 17 -column 6, line 32 --- -/--</p>	<p>1,6,7, 9-11,15, 16, 18-20, 22-24, 26,28-30</p>



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&\* document member of the same patent family

Date of the actual completion of the international search

22 August 2002

Date of mailing of the international search report

29/08/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Ströbeck, A.

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/31161

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>LOUIS S ET AL: "MANAGEMENT ISSUES FOR HIGH-PERFORMANCE STORAGE SYSTEMS" PROCEEDINGS OF THE 14TH. IEEE SYMPOSIUM ON MASS STORAGE SYSTEMS. STORAGE - AT THE FOREFRONT OF INFORMATION INFRASTRUCTURES. MONTEREY, SEPT. 11 - 14, 1995, PROCEEDINGS OF THE IEEE SYMPOSIUM ON MASS STORAGE SYSTEMS, LOS ALAMITOS, IEEE COMP. SOC. PRESS,, vol. SYMP. 14, 11 September 1995 (1995-09-11), pages 336-348, XP000597741 ISBN: 0-7803-3098-6 page 339, right-hand column, line 32 -page 342, left-hand column, line 19</p> <p>-----</p>	<p>1,4,5, 11,14</p>

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/31161

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5978845	A	02-11-1999	NONE

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
18 April 2002 (18.04.2002)

PCT

(10) International Publication Number  
**WO 02/32072 A2**

(51) International Patent Classification<sup>7</sup>: **H04L 29/00**

(21) International Application Number: PCT/US01/31161

(22) International Filing Date: 3 October 2001 (03.10.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/686,754 10 October 2000 (10.10.2000) US

(71) Applicant (for all designated States except US): **INTEL CORPORATION** [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HUSKINS, Jeffrey** [US/US]; 1931 West Bartlett Court, Chandler, AZ 85248 (US).

(74) Agents: **TROP, Timothy, N. et al.**; Trop, Pruner & Hu, P.C., 8554 Katy Freeway, Suite 100, Houston, TX 77024 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: **MANAGING REMOTE CLIENTS**



(57) Abstract: A messaging system may enable a server to assign unique identifiers to a plurality of clients. These identifiers enable a client to determine whether a message is specifically targeted to that client or, as an alternative, whether the client is a member of a group of targeted clients. A server may send messages containing an identifier to agents on one or more clients. The identifier may specify commands to manage the uploading of information from one or more clients to a server.



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

MANAGING REMOTE CLIENTSBackground

This invention relates generally to exchanging information in networks.

5       A multicast network may enable messages to be sent to a target group of clients that constitute a subset of all of the networked clients. Generally, multicasting is accomplished by including, within a header for example, the addresses of all the subject clients that are addressed.

10       A broadcast network operator may use a server or head end of a multicast network to control groups or individual broadcast receiver client platforms for the purposes of initiating network management sessions. These sessions may be for purposes of uploading network management information  
15 to the server or head end. This allows the network operator to manage the exchange of network management information in a very scalable fashion.

      Thus, there is a need for ways to enable the exchange of information between clients and a server, head end or  
20 broadcast network operator.

Brief Description of the Drawings

Figure 1 is a schematic depiction of one embodiment of the present invention;

Figure 2 is a flow chart for software resident on the  
25 client shown in Figure 1 in accordance with one embodiment of the present invention;

Figure 3 is a flow chart for software resident on the server or head-end in accordance with one embodiment of the present invention;

30       Figure 4 is a flow chart for software resident on the client shown in Figure 1 in accordance with another embodiment of the present invention;



Figure 5 is a flow chart for software resident on the server or head end in accordance with another embodiment of the present invention;

Figure 6 is a flow chart for software resident on the  
5 client shown in Figure 1 in accordance with another  
embodiment of the present invention; and

Figure 7 is a flow chart for software resident on the server or head end in accordance with another embodiment of the present invention.

10	Detailed Description
----	----------------------

Referring to Figure 1, a network may include at least one server, head-end or network operator 10 and a plurality of clients 12 (only one of which is shown). The server 10 may be coupled to a plurality of clients (including the client 12) through a distribution system that may be based on a wired system or a wireless or broadcast system. Examples of such networks include television distribution networks such as digital video broadcasting systems.

In one embodiment of the present invention, the server 10 may communicate with the clients 12 over a transport 14. The transport 14 may be in accordance with an analog or digital broadcasting system. As one example, the transport 14 may be compliant with the Digital Video Broadcast (DVB); Network-independent Protocol, ETS 300802, dated November 1997 and available from the European Telecommunications Standards Institute (ETS), Valbonne, France. The transport 14 may be a satellite, cable or airwave broadcasting system as examples.

In accordance with embodiments of the present invention, the client 12 recognizes messages directed individually to that client 12 from the server 10 or in some embodiments, from other clients 12. Bandwidth may be

conserved by addressing messages to a group of clients without the need to insert, within header, the individual identifiers of each of a large number of addressed clients.

In addition, the client 12 may include one or more addressable agents 44, 45, 46 and 48 that may be independently addressed by remote units such as the server 10. Moreover, by providing addressable agents 44, 45, 46 and 48 within a given client 12, messages that are specialized or which need specialized handling may be addressed to particular agents resident on the client 12 for appropriate handling.

The server 10 may include a network management command and control server 16. The server 16 is responsible for managing the collection of data from clients 12. The server 16 transmits messages which include a distinct service identifier (e.g., service\_id=0x02). The server 10 may also include an instant messaging or short message service (SMS) server 18 that also transmits messages having a distinct service identifier (e.g., service\_id=0x04).

In addition, a client disk management server 20 may be provided as well. The client disk management server 20 may transmit messages that include one or more distinct service identifiers (e.g., service\_id=0x01). In some cases, a variety of messages may be issued by the client disk management server 20 in order to initiate desired functions on a client's storage device or disk drive 43. For example, separate service identifiers may be utilized for the commands to create partitions, delete partitions, or modify partitions, as examples.

A data management session control server 21 may be responsible for handling the uploading of a data set that is uniquely identifiable on a client over an available return channel connection 47. This is a valuable capability that

allows the network operator to manage the mining of data and the scalability of the associated servers. A unidirectional message service type and message identifier may be used for a data management session control (DMSC) to manage data management sessions for groups of clients or individual clients. This group management is inherently supported by a unidirectional messaging service by the strategic assignment of client identifiers for all broadcast receiver clients in the network that are managed by the server 10.

10       The data management session control server 21 transmits messages that include one or more distinct service identifiers (e.g., service\_id=0x03). The server 21 creates a DMSC message data structure and passes information and data to the unidirectional messaging server 22 such as  
15       application-private data and data size, unique client identifier, a group flag which is a Boolean variable specifying if the client identifier is a group mask or individual client identifier, a service identifier value for the DMSC service and application-private message identifier.

20       In accordance with one embodiment of the present invention, the server 10 may implement a unidirectional messaging system. In a unidirectional messaging system, the server 10 may transmit messages to a plurality of clients that are unable to respond in any way. One example of such  
25       a network is a direct-to-home (DTH) broadcast network that may be compliant with the DVB protocol. The network may use a connection oriented communication protocol or a real time connectionless communication protocol as two examples. There are many applications of unidirectional messaging from  
30       server to client such as instant messaging, command and control and notification and signaling, as examples. In other cases, the network may be a bidirectional network, for example with an Internet Protocol (IP) multicast backbone.

In one embodiment of the invention, the server 10 may include a unidirectional messaging server (UMS) 22 that is coupled to the servers 16, 18, 20 and 21 to generate messages in an appropriate format. The messages transmitted  
5 by the UMS server 22 may include messages originally generated by one of the servers 16, 18, 20 or 21. The UMS server 22 may then be coupled to an Internet Protocol multicast module 24 that places the messages in an appropriate multicast protocol format. Finally, a DVB  
10 Multiprotocol Encapsulation (MPE) 26 is coupled to the Internet protocol multicast module 24. The MPE is described in DVB Specification for Data Broadcasts (EN 301 192) and Specification for Service Information (SI) in DVB Systems (EN 300 468 V1.3.1 1998-02) both available from the ETS.  
15 The output of the DVB MPE 26 and a DVB-Service Information (SI) generator 28 are coupled to the transport 14. Service Information is digital data describing the delivery system, content and scheduling/timing of broadcast data streams.

In the client 12, the stream from the DVB-SI generator  
20 28 is coupled to a DVB-SI receiver 40 and service acquisition module 38. The service acquisition module 38 extracts a program identifier (PID) and provides it to a DVB demultiplexer 32. A tuner 30 may tune the client 12 to the appropriate channel corresponding to the extracted program  
25 identifier.

The message from the DVB MPE 26 is provided to a DVB MPE receiver 42. The receiver 42 communicates with an IP multicast module 40 and a unidirectional messaging server 38. The server 38 breaks down the message to determine  
30 whether a service identifier was included in the data stream. If so, the message is forwarded to an appropriate agent designated to receive messages with particular service identifiers.

A disk management agent 44 may be coupled to a disk drive controller 47 in turn coupled to a storage device 43 that may, for example, be a hard disk drive. The disk management agent 44 may be addressed as a message recipient  
5 by the client disk management server 20. The disk management agent 44 may cause processes to be undertaken through the controller 47 that in turn control the use of the storage device 43. This control may include determining what information is stored on the storage device 43 and how  
10 that information is stored on the storage device 43.

In one embodiment of the present invention, the network management command and control server 16 may provide a specific message identifier that causes its message to be received by a network management session management agent 48  
15 tuned to a particular service identifier. Similarly, messages from the instant messaging server 18 may include a service identifier that cause those messages to be forwarded to the agent 48 in the client 12. Likewise, messages from the data management session control server 21 may have  
20 appropriate identifiers that cause them to be shunted to the data management session control agent 45 on the client 12.

The server 10 may include a storage 25 that stores software 134, 70 and 102 for controlling the operation of the server 22. Likewise, the server 38 on the client 12 may  
25 be coupled to a storage 43 that stores software 50, 82 and 114 that controls the operation of the server 38. The servers 22 and 38 may also be processor-based systems.

Turning next to Figure 2, the software 50 on the client 12 initially receives the unidirectional messaging server  
30 address and port from the server 10. The client 12 may also be assigned a client identifier as indicated in block 52. Thus, an Internet Protocol multicast system may be established wherein each client has a UMS address and port

as well as a unique client identifier, assigned by the server 10. In some embodiments, the server 10 may dynamically adjust addresses and ports as well as client identifiers to enable communication of particular messages, message groups or types of messages to particular clients in a dynamic and reconfigurable fashion.

Having received its address, port and client identifier, the client 12 receiver joins a multicast group and listens for messages addressed specifically to it or to any groups that the client 12 belongs to, as indicated in block 54.

A disk management agent 44 registers its service identifier with the UMS server 38 as indicated in block 56. When the UMS server 38 receives a packet with a UMS message, as indicated in block 58, a check determines whether the particular client 12 is the intended recipient as indicated in diamond 60. If not, the message is discarded as indicated in block 62.

However, if the particular client 12 is the intended recipient, the server 38 checks the message's service identifier and passes the message to the correct agent 44, 46 or 48, as indicated in block 64. The message is then delivered to the appropriate agent 44 as indicated in block 66. In the agent 44, the information is parsed and passed to an appropriate process for handling as indicated in block 68.

For example, when addressed, the disk management agent 44 sends appropriate commands to the controller 47 for relay to the storage device 43. Dependent on the service identifier accompanying the message, the agent 44 may provide appropriately translated commands to the controller 47 such as the commands to create a partition, delete a partition or modify a partition. Each of these commands may

be given separate service identifier values such as 0x03, 0x04 and 0x05. The disk management agent 44 may translate a message with a service identifier value into an appropriate format for the controller 47 based on the message received from the client disk management server 20. For example, with a message that includes a service identifier value 0x03, the agent 44 may issue a command to the controller 47 to partition the storage 43.

On the server side, shown in Figure 3, the network software 70 begins by assigning multicast addresses and ports for unidirectional messaging service to a plurality of clients 12 as indicated in block 72. The server 10 may also assign client identifiers in a dynamic and reconfigurable fashion. The address, port and client identifiers are then transmitted to the clients as indicated in block 74.

Thereafter, the disk management server 20 may create a data structure and pass this data structure to the server 22 as indicated in block 76. The server 22 creates a unidirectional message and assigns a client value, sets a group flag, and copies private data in the private bytes of the message as indicated in block 78. More particularly, a unique client identifier may be assigned. The client identifier may either be a particular preassigned client identifier or, as one example, may be zero when multiple clients are targeted. A group flag may be a Boolean value specifying whether the client identifier is a group mask or a particular identifier. A group mask is an identifier that identifies a subset of the clients 12 on the network. This subset may include a plurality of clients but less than the total number of addressable clients.

As one example of a unidirectional message header, the message may include a number of variables including a group\_mask, a service\_id, a version\_id, a message\_id, and a

private\_data\_byte. The group\_mask may, in one embodiment of the present invention, include 64 bits, the service\_id may include eight bits, the version\_id may include sixteen bits, the message\_id may include eight bits and the

5 private\_data\_byte may include eight bits. The version\_id is the version of the unidirectional messaging protocol and may initially be set to zero. The service\_id may be a service identifier that may be as one example 0x02 for an instant messaging service. Advantageously, the message size does

10 not exceed 1,024 bytes in order to eliminate potential datagram fragmentation. The group\_filter may be used in conjunction with the client\_id field to limit the size of the private data bytes required for an application. Each of header items may include an unsigned integer most

15 significant bit first (uimsbf) identifier in accordance with the DVB specification except for the private\_data\_byte which may include a bit string, left bit first (bslbf) identifier.

As indicated in block 80, the message is then sent to all the clients 12 on the network. Each client then

20 determines whether the message is intended for that client. The client 12 determines whether it is the specific intended recipient by determining whether the message is addressed to the client identifier of the client 12. For example, using an AND logic operator between the message's identifier and

25 the client's identifier, the client 12 may determine if the client 12 is within a group of clients jointly addressed by the server 10.

In one embodiment of the present invention, distinct groups of users may receive common client identifier

30 elements. Thus, a plurality of clients whose owners have signed up for enhanced service may include a common code portion in their client identifier. When a message including that common code portion in the client identifier



is received, each of those clients accepts the message. Likewise, clients in particular geographic areas, having particular interests or otherwise identifiable clients may be given unique prefixes/suffixes or identifier code portions. The code portion may be logically ANDed with a group\_mask to determine whether a particular client is a member of the targeted group.

The management message header may also include fields to address the disk management agent 44, such as a volume\_name\_len field that provides the volume, name, length and bytes for the pertinent volume of a storage device 45 in the form of a hard disk drive. In one embodiment of the present invention, that field may be eight bits long and may be have a bslbf identifier. In addition, a volume\_name\_byte field may give the volume name bytes that make up the name of the volume to mount on which to create a partition. In one embodiment of the present invention, this field may be eight bits long and may include a bslbf identifier. Finally, a partition\_size field may give the size of the partition to create in bytes. This field may be thirty-two bits in size and may use the uimsbf identifier. Of course, additional fields and additional service identifiers may be utilized to implement still additional commands to the client storage device 45.

In this way, the client disk management server 20, under the direction from the server or head-end 10, may control how the storage 43 is set up and utilized on a targeted client 12 or a targeted group of clients 12. Each of the clients 12 may be individually addressed, the entire set of clients may be addressed or any subgroup of clients may be collectively addressed such that their storage devices 45 may be individually or collectively modified.

Thus, the storage devices 43 of one or more clients may be selectively controlled from the server 10.

Referring to Figure 4, the software 82 on the client 12 for implementing a network management session, initially receives the unidirectional messaging server address and port from the server 10. The client 12 may also be assigned a client identifier as indicated in block 84. Thus, an Internet Protocol multicast system may be established wherein each client has a UMS address and port as well as a unique client identifier, assigned by the server 10.

Having receives its address, port and client identifier, the client 12 receiver joins a multicast group and listens for messages addressed specifically to it or to any groups that the client 12 belongs to, as indicated in block 86.

A data management session control agent 45 registered its service identifier with the UMS server 38 as indicated in block 88. When the UMS server 38 receives a packet with a UMS message, as indicated in block 90, a check determines whether the particular client 12 is the intended recipient as indicated in diamond 92. If not, the message is discarded as indicated in block 94.

However, if the particular client 12 is the intended recipient, the server 38 checks the message's server identifier and passes the message to the correct agent 45, as indicated in block 64. The message is then delivered to the appropriate agent 45, as indicated in block 98. In the agent 45, the information is parsed and passed to an appropriate process for handling as indicated in block 100.

The data management session control agent 45 receives a targeted message from the data management session control server 21 and in response thereto provides the data requested by the server 21, for example over a back channel

47. Thus, in one embodiment, the agent 45 may receive messages having a particular syntax including a ManagementMessage() which includes a group\_mask, a service\_id, a version\_id, a message\_id, a message\_byte\_count, and a DMSessionControlMessage() that in turn includes a session\_id, a session\_host\_name, a session\_start\_time, a session\_duration and a data\_id.

The session\_id is a unique session identifier. The server\_host\_name is a string host name of the data management server to establish a connection. The session\_start\_time is a date and time for the client 12 to establish the session. The session\_duration is the duration after start time that the server 21 will accept the session and provides a time window if necessary. The data\_id is a unique identifier of information or data set to exchange during the session. The method for managing and assigning information and/or data of the identifier is application private.

Thus, the server 21 can initiate a message to the client 12 which causes the client 12 to initiate an uploading of specified data at a specified time. That is, the server 21 may specify a header including a session\_id, a server\_host\_name, a session\_start\_time, a session\_duration, and a data\_id, and in response thereto the data management session control agent 45 gathers the requested information and provides it in the requested form at the requested time.

The server 21 may provide messages with different message identifiers including a session create message, a session delete message and session update message, as examples. The session delete message simply deletes a previously created session and the session update message causes additional information to be provided for a scheduled session.

In one embodiment of the present invention, the group\_mask may include 64 bits with the uimbsf identifier. The session\_id may include eight bits with a uimbsf identifier. The version\_id may include sixteen bits with a uimbsf identifier. The message\_id may include eight bits and have an identifier of 0x01. The message\_byte\_count may include sixteen bits within a uimbsf identifier. The DataManagementSessionControlMessage() may include the syntax session\_id with eight bits, session\_start\_time with sixty-four bits, session\_duration with thirty-two bits, and data\_id with thirty-two bits in one embodiment, all in the uimbsf identifier format. The DataManagementSessionControlMessage() may also include a server\_host\_name with one hundred twenty-eight bits with a bs1bf identifier.

On the server side, shown in Figure 5, the network software 102 begins by assigning multicast addresses and ports for unidirectional messaging service to a plurality of clients 12 as indicated in block 104. The server 10 may also assign client identifiers in a dynamic and reconfigurable fashion. The address, port and client identifiers are then transmitted to the clients as indicated in block 106.

Thereafter, the data management session control server 21 may create a data structure and pass this data structure to the server 22 as indicated in block 108. The server 22 creates a unidirectional message and assigns a client value, sets a group flag, and copies private data in the private bytes of the message as indicated in block 110. More particularly, a unique client identifier may be assigned. The client identifier may either be a particular preassigned client identifier, or as one example, may be zero when multiple clients are targeted. A group flag may be a Boolean value specifying whether the client identifier is a

group mask or a particular identifier. A group mask is an identifier that identifies a subset of the clients 12 on the network. This subset may include a plurality of clients but less than the total number of addressable clients.

5       As indicated in block 112, the message is then sent to all the clients 12 on the network. Each client then determines whether the message is intended for that client. The client 12 determines whether it is the specific intended recipient by determining whether the message is addressed to  
10   the client identifier for the client 12. For example, using an AND logic operator between the message's identifier and the client's identifier, the client 12 may determine if the client 12 is within a group of clients jointly addressed by the server 10.

15       The network management command and control server 16 works with the network session management agent 48. When a message generated at the instance of the server 16 is directed to the agent 48, the agent 48 calls the session manager 49. The session manager may provide the desired  
20   management information in a predetermined format over a back channel 43 in one embodiment of the present invention.

      The network management sessions are generally for the purposes of uploading network management information to the server 16. As one example, a management information base  
25   (MIB) may be uploaded over a simple network management protocol (SNMP) over the return channel 43. The operation of the agent 48, shown in Figure 6, generally corresponds to that described previously with respect to the agents 44 and 45. That is, the UMS addresses, port and client identifiers  
30   are received, as indicated in block 116, the receiver joins the multicast group and listens for messages as indicated in block 118 and the network session management agent 48 registers its service identifier with the UMS receiver as

indicated in block 120. The UMS receiver then receives the package with the message as indicated in block 122.

A check at diamond 124 determines whether the particular agent 48 is the intended recipient. If not, the message is  
5 discarded as indicated in block 126. Otherwise, the receiver checks the service identifier and passes the message to the agent 48, as indicated in block 130. The information is parsed and passed to the session manager 49. The session manager 49 then schedules the session, using the channel 43,  
10 with the server 16.

The message format is basically the same as the format used by the DMSC. However, instead of having  
DMSessionControlMessage(), an NMSessionControlMessage()  
includes an info\_ID field. The info\_ID field is a unique  
15 identifier of information or a data set to exchange during the session. The method of managing and assigning the information and/or data set identifier is application private. For example, a specific SNMP client MIB may be identified to upload to the server, if the client manages  
20 multiple MIBs.

An MIB is information on an agent that is known as the management information base. This information forms a basis for event reporting. The standards for MIBs are set forth for example in RFC 1229 distributed by the Network Working  
25 Group (May 1991).

Turning next to Figure 7, the operation of the network management server 16, utilizing the software 134, corresponds generally to that described previously. Again, the multicast address and port for UMS is assigned and the client  
30 identifiers are assigned as indicated in block 136, the UMS address and port and client identifier are sent to the clients as indicated in block 138, and the network management command and control server 16 creates a data structure and

passes the data to the UMS server as indicated in block 140. The UMS server 22 then creates the UM message, assigns a client value, sets a group flag and copies private data into private bytes of the message as indicated in block 142.

5    Thereafter, the message is sent (block 144).

Then at the predetermined time, the server 16 receives the scheduling information from the session manager 49. At the appropriate time, a session may be provided in which the MIBs or other information is uploaded to the server 16 via  
10   the actions of the agent 48 and session manager 49.

In one embodiment of the present invention, distinct groups of users may receive common client identifier elements. Thus, a plurality of clients whose owners have signed up for enhanced service may include a common code  
15   portion in their client identifier. When a message including that common code portion in the client identifier is received, each of those clients accepts the message.

While the present invention has been described with respect to a limited number of embodiments, those skilled in  
20   the art will appreciate numerous modifications and variations therefrom. It is intended that the appended claims cover all such modifications and variations as fall within the true spirit and scope of this present invention.

What is claimed is:

1. A method comprising:  
5 receiving on a client a message from a server  
addressed to said client; and  
scheduling a data upload session based on said  
message.
2. The method of claim 1 further comprising:  
10 assigning an individual identifier to the clients  
comprising a set of clients including said client;  
assigning a group identifier to a subset of the  
clients within the set of clients; and  
enabling said client in said set to determine  
15 whether a message is sent to said client or to the subset.
3. The method of claim 2 including sending a message  
to a client in a unidirectional messaging system.
4. The method of claim 1 including receiving a  
message including an identifier which specifies a task to  
20 perform on a storage device.
5. The method of claim 4 including receiving a  
message including an identifier indicating a change to a  
partition on said storage device.
6. The method of claim 1 including locating an  
25 identifier within said message that specifies an agent on  
said client to handle said message, and forwarding said  
message to said agent.



7. The method of claim 6 including enabling said agent to upload said data to said server over a back channel.

8. The method of claim 6 further including extracting  
5 a specified time from said message and uploading said data at the specified time.

9. The method of claim 1 including extracting from said message an identifier which specifies the information to upload to said server and uploading the specified  
10 information to said server.

10. The method of claim 9 wherein said message includes a server identifier, and uploading said data to the identified server.

11. An article comprising a medium storing  
15 instructions that enable a processor-based system to:  
receive a message from a server addressed to said system; and  
schedule the uploading of information from said system to said server based on said message.

20 12. The article of claim 11 further storing instructions that enable a processor-based system to:  
assign an individual identifier to each of the clients comprising a set of clients including said system;  
assign a group identifier to a subset of the  
25 clients within the set of clients; and  
enable the system to determine whether a message is sent to the system or to the subset.

13. The article of claim 12 further storing instructions that enable the processor-based system to send a message to a client in a unidirectional messaging system.

14. The article of claim 11 further storing  
5 instructions that enable the processor-based system to decode a command within said message to modify the storage of information on a storage device.

15. The article of claim 11 further storing instructions that enable the processor-based system to  
10 locate an identifier within said message that specifies an agent on said system to handle said message, and forward said message to said agent.

16. The article of claim 15 further storing instructions that enable said processor-based system to  
15 upload said data to said server over a back channel.

17. The article of claim 15 further storing instructions that enable the processor-based system to extract a specified time from said message and upload said data at the specified time.

20 18. The article of claim 11 further storing instructions that enable the processor-based system to extract from said message an identifier which specifies the information to upload to said server and upload the specified information to said server.

25 19. The article of claim 18 further storing instructions that enable the processor-based system to upload said data to a server identified in said message.

20. A system comprising:  
a processor-based device; and  
a storage storing instructions that enable said  
processor-based device to receive a message from a server  
5 addressed to said processor-based device and schedule the  
uploading of information to said server based on said  
message.

21. The system of claim 20 wherein said storage stores  
instructions that enable the device to compare a group  
10 identifier in a message to determine whether the device is  
within a group addressed by said server.

22. The system of claim 20 wherein said storage stores  
instructions that enable said processor-based device to  
locate an identifier within said message that specifies an  
15 agent on said device to handle said message and forward said  
message to said agent.

23. A method comprising:  
transmitting a message to a client; and  
scheduling the uploading of information on said  
20 client based on said message.

24. The method of claim 23 further storing  
instructions that enable the processor-based system to  
receive an upload of data over a back channel from a client.

25. The method of claim 24 including transmitting a  
time specification in the message and receiving an upload of  
25 data from a client at said specified time.

26. An article comprising a medium storing  
instructions that enable a processor-based system to:  
transmit a message to a client; and  
schedule the uploading of information to said  
5 system based on said message.


27. The article of claim 26 further storing  
instructions that enable the processor-based system to  
transmit information in said message that specifies a time  
for an information upload from said client.

10 28. The article of claim 26 further storing  
instructions that enable the processor-based system to  
transmit a message that specifies the information that the  
client should upload.

29. A system comprising:  
15 a processor-based device; and  
a storage storing instructions that enable said  
processor-based device to transmit a message to a client and  
schedule the uploading of information on said client to said  
system based on said message.

20 30. The system of claim 29 wherein said storage stores  
instructions that enable the processor-based device to  
specify how information is provided from the client to said  
system.

25



2/7




Fig. 2

3/7




Fig. 3

4/7




Fig. 4



5/7




Fig. 5

6/7




FIG. 6

7/7




FIG. 7